

# EXTENSION LEAD PNEL

## A COST-EFFECTIVE SOLUTION, WHEREVER YOU NEED POWER

Built to the highest standards for exceptional reliability, the SA POWERNET EX Extension Leads deliver **power to hazardous areas effectively and with minimum hassle**. ATEX compliant, tough and durable, compatible with all SA lighting equipment and supplied ready to use.



### BENEFITS

- ATEX Certified for Zones 1 and 2 (gas), 21 and 22 (dust)
- INMETRO Certified
- Tough and durable
- Fast delivery times
- Waterproof and dustproof

### SPECIFICATIONS

#### CERTIFICATION

Ex II 2 GD  
Ex de IIC T5 Gb  
Ex tb IIIC T100°C Db IP66

#### INGRESS PROTECTION

IP66

#### OPERATING TEMPERATURE

-20°C to +40°C

#### VOLTAGE

24VAC, 42VAC, 110VAC, 230VAC, 400VAC

#### INPUT

1 x 16A Plug  
(32A on 400VAC)

#### OUTPUT

1 x 16A Mobile Socket  
(32A on 400VAC)

#### WEIGHT

6kg (HOFr) - 15m Extension Lead

### CORE PRODUCT INFORMATION

**SA POWERNET EX Extension Lead 24V** c/w 1 x 16A ATX plug, 1 x 16A ATX socket and 20m of braided HOFr cable [HRE], [Operating Temp -15°C to +40°C]  
**Order Code: PNEL24EX20HRE/ATX16/3P**



**SA POWERNET EX Extension Lead 110V** c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket, and 15m of braided HOFr cable **Order Code: PNEL110EX15HRE/CEA16/3P** and 25m of braided HOFr cable **Order Code: PNEL110EX25HRE/CEA16/3P**



**SA POWERNET EX Extension Lead 230V** c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket, and 15m of braided HOFr cable **Order Code: PNEL230EX15HRE/CEA16/3P** and 25m of braided HOFr cable **Order Code: PNEL230EX25HRE/CEA16/3P**



**SA POWERNET EX Extension Lead 400V** c/w 1 x 32A 4P CEAG plug, 1 x 32A 4P CEAG socket, and 25m of braided HOFr cable [HR]  
**Order Code: PNEL400EX25HR/CEA32/4P**



ATX & STAHL connectors and other cable types and other voltages also available - please contact SA Equip for more details.

