



LED TOWER LIGHT

SAAL25/TW

HIGH PERFORMANCE ATEX LIGHTING TOWER

The SA LUMIN LED Tower Light is a rugged fully ATEX & IECEx certified transportable light, providing **high quality illumination for medium to large sized areas** with a powerful spread of light. With an integrated manual hand trolley and 5m transportable mast, the SA LUMIN LED Tower Light **can be easily positioned and maneuvered** to accommodate your needs. The adjustable light head with secure positioning bolt allows efficient angling of the light in both upwards and downwards directions.



BENEFITS

- ATEX & IECEx certified for Zones 1 and 2 (Gas)
- Light output 25,000 lumens
- -50°C to +50°C Operating Temperature (Based on Plug Type)
- Easy plug-and-play application
- 6000K+ colour temperature
- Large spread of high power light
- Durable construction
- Safety cord for additional protection
- 5 year product warranty

SPECIFICATIONS

CERTIFICATION

EX II 2 G D
EX db eb mb op is IIB T4 Gb
EX tb op is IIIC T104°C Db

INGRESS PROTECTION

IP66

VOLTAGE OPTIONS

110VAC, 230VAC

PLUG OPTIONS

ATX, CEAG, Stahl

OPERATING TEMPERATURE

-50°C to +50°C

LIGHT OUTPUT

25,000 lumens

LIGHT SOURCE

High Power LEDs

DIMENSIONS

Light Head
460mm x 385mm x 850mm

Mast Extended
2150mm x 2150mm x 5500mm

Mast Folded
300mm x 300mm x 1750mm

WEIGHT

105kg (Excluding cable and plug)

CORE PRODUCT INFORMATION

SA LUMIN EX LED Tower Light 110V
c/w CEAG plug and 20m of braided cable
Order Code: SAAL25-110/TW/CEA/20HRE

SA LUMIN EX LED Tower Light 230V
c/w CEAG plug and 20m of braided cable
Order Code: SAAL25-230/TW/CEA/20HRE

Different combinations of plugs and cable lengths also available – please contact SA Equip for more details.



LIGHT