

# HEATER

SAPH18440

---



## WHERE POWERFUL PERFORMANCE MATTERS

THE SA FLEXIHEAT EX HEATER withstands the harshest conditions offering robust, reliable and powerful performance for a range of industry applications. The lightweight, ergonomic design offers increased portability across work sites. Fully certified for use in hazardous zones classified as 1 or 2, the Heater comes as 'Plug & Play' enabling efficient implementation and use of the system. Hosting optimised heating element design and a solid state electronic control system, our 440V Heater allows you to meet temperature requirements effectively and maintain optimum working conditions in temperatures as low as -40°C. If you're not using the SA FLEXIHEAT EX Heater, you're out in the cold.

---

# HEATER

## SAPH18440

### BENEFITS

- ATEX certified for Zones 1 & 2 (gas)
- 400-440VAC (+/-10%)
- Compact, portable and lightweight
- Operational in temperatures as low as -40°C
- IP65 Rated
- 18kW Output at 440V
- Produces Airflow at 2560m<sup>3</sup>/HR
- Solid state electronic control system
- Marine grade materials
- Multiple lifting handles
- Optimised heating element design
- Can be used with or without ducting
- Compatible with SA CYCLONE DUCTING
- Compatible with SA POWERNET MDU



### SPECIFICATIONS

**CERTIFICATION**

II 2 G c IIB T3  
Ex db e mb IIB T3 Gb

**OPERATING TEMPERATURE**

-40°C to +40°C

**INGRESS PROTECTION**

IP65

**DIMENSIONS**

760mm x 560mm x 560mm  
(L x w x h)

**WEIGHT**

55kg exc. cable

**CURRENT DRAW @ 440VAC**

Start Up: 32A

Run: 26A

**FREE AIRFLOW**

2130m<sup>3</sup>/h (1253cfm) @ 50Hz

2560m<sup>3</sup>/h (1506cfm) @ 60Hz

**DUCTING SIZE**

300mm diameter

**3 PHASE SUPPLY**

3Ph+E or 3Ph+N+E

**AIR SPEED**

15.5m/s (51ft/s) @ 50Hz

16.3m/s (54ft/s) @ 60Hz

**TYPICAL TEMPERATURE RISE**

Approx. 20°C above ambient

**NOISE LEVEL @ 1M**

83dba

**CABLE LENGTH**

10m (or as required)

PATENT PROTECTED GB2524076

### CORE PRODUCT INFORMATION

SA FLEXIHEAT EX Heater 18kW 400V-440V (+/-10%)  
3Ph 50/60 Hz c/w 4p 32A CEAG Plug and 10m of braided cable  
**Order Code: SAPH18440/10HR/CEA32/4P**



SA FLEXIHEAT EX Heater 18kW 400V-440V (+/-10%)  
3Ph 50/60 Hz c/w 4p 32A CEAG Plug and 20m of braided cable  
**Order Code: SAPH18440/20HR/CEA32/4P**



**CEAG 5P & STAHL 5P** plugs and different cable lengths also available – please contact SA Equip for more details.

